



KONICA MINOLTA

## Environmental Data Sheet for bizhub 4750i

Version 0.5

Date: 12.11.2020

Revision date:

Page 1 of 4

<b>1 <u>Company</u></b>			
Manufacturer/Supplier:	Konica Minolta Business Solutions Europe GmbH	Tel.:+49/511/7404-0	
Address:	D-30855 Langenhagen, Europaallee 17	Fax:+49/511/741050	
<b>Before getting back to the editor, please contact your local support first</b>			
Editor:	Konica Minolta, Sustainability Management, IMD	Tel.:+49/511/7404-361	
	Markus Kelch	Fax:+49/511/7404-396	
	<a href="mailto:markus.kelch@konicaminolta.eu">markus.kelch@konicaminolta.eu</a>		

<b>2 Tests / Approvals / Declarations</b>			
2.1	CE Conformity:	Declaration of Conformity	For this product an EU Declaration of Conformity according to EN17050-1 is available. It can be obtained from the editor on request.
2.2	EU-Directives:	2014/35/EU 2014/30/EU 2009/125/EC 2011/65/EC	This product is in compliance with the listed EU directives: - Low Voltage Directive / Product Safety - EMC Directive / Electromagnetic Compatibility - ErP Directive / Eco Design - RoHS2 Directive and amendments
2.3	Safety Tests:	GS Mark S 504 256 29 Nemko Mark P 202 245 30 /A1	TUEV Rheinland EN 62368-1 NEMKO, Norway EN 62368-1
2.4	EAC Certification:	RU C-JP AR46 B14120 (0252562)	EAC certificate
2.5	Electromagnetic Compatibility (EMC):	EMC Mark CJ 504 671 59	TUEV Rheinland EN55032:2012, EN61000-3-2:2014, EN61000-3-3:2013, EN55024:2010, CISPR 32:2012, CISPR 24:2010
2.6	ENERGY STAR:	ENERGY STAR program compliance	EPA based (version 3.0) This product is listed in ENERGY STAR databases
2.7	Eco Design Directive:	2009/125/EC 1275/2008/EC Voluntary Agreement on Lot 4	Framework for the setting of ecodesign requirements for energy-related products Requirements for electrical power consumption in standby and off-mode Konica Minolta is signatory of the EVAP
2.8	Blue Angel Mark:	German environmental label is applied	RAL RAL-UZ 205
2.9	Document Authenticity:	PTS certificate will be applied Printer: Copier: ISO 11798 will be applied	Papiertechnische Stiftung (PTS) Ordinance for Lawyers and Notaries in Germany (DONot), § 29; RISE (Sweden) According Swedish National Archive Regulations relevant test conditions were noted down in the according test certificate!
2.10	Laser safety	EN 60825-1 : 2014	Class 1 laser
2.11	Quality and Environmental Management:	ISO 9001 certification ISO 14001 certification	This product was manufactured under a certified Quality Management System according to ISO 9001 and under a certified Environmental Management System according to ISO 14001.



### Environmental Data Sheet for bizhub 4750i

<b>3 General Information</b>			
3.1	Speed:	Pages per minute Printing Copying	Black and White 47 (ISO 24734) 47 (ISO 24735)  Colour
3.2	Weight:	About 34.9 kg	Basic System only
3.3	Dimensions / Volume:	420 mm 528 mm 572 mm 126.8 litre	Width Depth Height Volume (calculated)  Basic System only
3.4	Environmental programmes:	This product conforms to the following voluntary environmental programme requirements:	Konica Minolta Environmental Policy Konica Minolta Product Environmental Assessment All production sites have ISO 14001 certification. Konica Minolta Environmental Report including environmental accounting report is published annually. <a href="https://www.konicaminolta.com/about/csr/environment/in dex.html">https://www.konicaminolta.com/about/csr/environment/in dex.html</a>
3.5	Extension of product lifetime:	The manufacturer offers on a voluntary base:	Spare parts availability: 5 years after end of production Service availability: 5 years after end of production (depends on service level agreement, business to business)  Warranty: Depends on service level agreement, business to business
3.6	Materials:	This product contains no*:	Cadmium (< 0.01%) Lead Hexavalent chromium Mercury (except for a fluorescent lamp) PBB and PBDE (Polybrominated biphenyls and their ethers contained in mechanical plastic parts in concentrations exceeding the natural background levels) Ozone depletion substances, according to those categories that are already banned in the Montreal protocol Chloroparaffines with chain length 10-13 atoms, chlorination greater than 50% contained in mechanical plastic parts PCB or PCT Large-size plastic case parts (weighing more than 25g) do not contain the halogenated flame proofing agents. Asbestos * Impurity threshold level: less than 0.1%

<b>4 Emissions / Consumption</b>																															
4.1	Operation noise: (Measured values)	Sound power, Lwa <sup>1)</sup>  Sound power declared, Lwad  Sound pressure, operator position, Lpa <sup>2)</sup>	<table border="1"> <thead> <tr> <th colspan="2">Black and White</th> <th colspan="2">Colour</th> </tr> </thead> <tbody> <tr> <td>Standby</td> <td>nm</td> <td>Standby</td> <td>dB(A)</td> </tr> <tr> <td>Printing</td> <td>67.8 dB(A)</td> <td>Printing</td> <td>dB(A)</td> </tr> <tr> <td>Standby</td> <td>nm</td> <td>Standby</td> <td>dB(A)</td> </tr> <tr> <td>Printing</td> <td>70.8 dB(A)</td> <td>Printing</td> <td>dB(A)</td> </tr> <tr> <td>Standby</td> <td>28.7 dB(A)</td> <td>Standby</td> <td>dB(A)</td> </tr> <tr> <td>Printing</td> <td>57.9 dB(A)</td> <td>Printing</td> <td>dB(A)</td> </tr> </tbody> </table> <p>Basic unit without accessories 1) measured and declared according to ISO7779, RAL-UZ 205 2) workspace related emission value, operator test position: height=1.50m; distance=0.25m in front of the panel position nm Not measured nd There is no noise in ready mode two minutes after the last printout</p>	Black and White		Colour		Standby	nm	Standby	dB(A)	Printing	67.8 dB(A)	Printing	dB(A)	Standby	nm	Standby	dB(A)	Printing	70.8 dB(A)	Printing	dB(A)	Standby	28.7 dB(A)	Standby	dB(A)	Printing	57.9 dB(A)	Printing	dB(A)
Black and White		Colour																													
Standby	nm	Standby	dB(A)																												
Printing	67.8 dB(A)	Printing	dB(A)																												
Standby	nm	Standby	dB(A)																												
Printing	70.8 dB(A)	Printing	dB(A)																												
Standby	28.7 dB(A)	Standby	dB(A)																												
Printing	57.9 dB(A)	Printing	dB(A)																												



**Environmental Data Sheet for bizhub 4750i**

**4 Emissions / Consumption**

4.2 Energy (measured values)

Power  
Max power consumption <sup>3)</sup>  
Average power consumption <sup>4)</sup>

	Power [Watt]	Mode (230V)
Max.	1019	Starting
Printing	560	Operating
Standby	54	Without energy-save
	39	With energy-save
	0.5	Sleep mode
	0.106	Plug-in off mode

Recovery times

Time [seconds]	Recovery from mode
8	Energy-save mode
8	Sleep mode

Applied standard test method: RAL-UZ 205

3) Short-term maximum value, for mains fuse calculation

4) Calculation basis for power consumption

TEC

Version 3.0: 0.57 kWh/week  
Only for reference:  
Version 2.0: 2.0 kWh/week

Typical Energy Consumption value, weekly base, according to the definitions of ENERGY STAR (230V)

Heat Generation (calculated)

Printing	2,016 kJ/h	
	11.5 BTU/h	BTU 230V, based on the TEC value of this product (24 h x 7 days)
Standby	194.4 kJ/h	Without energy-save

4.3 Emissions: (Measured values)

Substances

- Ozone
- Styrene
- Benzene
- TVOC
- Fine dust

Operation (Printing)	Emission rate [mg/h]	Concentration <sup>5)</sup> [mg/m <sup>3</sup> ]
Standby	nm	
Operating b/w	0.270 mg/h	0.014 mg/m <sup>3</sup>
Standby	nm	
Operating b/w	0.849 mg/h	0.042 mg/m <sup>3</sup>
Standby	nm	
Operating b/w	0.001 mg/h	<0.001 mg/m <sup>3</sup>
Standby	0.031 mg/h	0.002 mg/m <sup>3</sup>
Operating b/w	5.541 mg/h	0.277 mg/m <sup>3</sup>
Standby	nm	
Operating b/w	0.830 mg/h	0.042 mg/m <sup>3</sup>

Test conditions

Basic system without options / accessories

Test conditions according to RAL-UZ 205. Emission rate in mg/h.

5) - Calculation to evaluate the ambient air concentration rate in mg/m<sup>3</sup>: Room size 40 m<sup>3</sup>, Air exchange rate 0.5/h, and Multi operating cycles.

nd = not detectable (below the detection limit)

nm = not measured

Regular maintenance assumed. Measured values were evaluated on basis of one machine. Values may vary within production.



### Environmental Data Sheet for bizhub 4750i

5	<b>Consumables and other items</b>												
5.1	Toner:	black, for bizhub 4050i, bizhub 4750i (TNP90)	<p>Components: Styrene acrylic resin, polyester resin, ferrite (iron oxide and manganese oxide), carbon black, wax, amorphous silica, organic pigment (&lt;1%).</p> <p>Flashpoint over 350 °C.</p> <p>When used as intended (toner for office copies) no danger for health and environment.</p> <p>Avoid dusting.</p> <p>Test on mutagenic activity (AMES) showed negative results.</p> <p>Classification class for endangerment of water: WGK = 1 (Germany, slightly endangering water)</p> <p>Waste toner classification no.(EWC): 080318, GC020, green list, not hazardous waste</p> <p>Polymerized toner reduces environmental impacts (CO<sub>2</sub>, NO<sub>x</sub> and SO<sub>x</sub> emissions during production of toner) by about 40% compared to conventional toners.</p>										
5.2	Waste toner box:	1 box	Must be replaced after 36,000 printouts										
5.3	Photoconductor:	Photoconductor for: bizhub 4050i, bizhub 4750i	Aluminium tube coated with organic material.										
5.4	Filters:	This product contains 1 filter	Must be replaced after 200,000 printouts										
5.5	Batteries:	1 lithium battery (CR2032)	<p>The batteries are in conformity with: 2006/66/EC (battery and accumulators).</p> <p>The product documentation contains information about proper disposal, which should be followed</p>										
5.6	Light source:	Scanner lamp	LED										
5.7	Recycling paper	Papers according to EN 12281:2002 are suitable for use	Storage in climate-proof packaging recommended										
5.8	Packaging material:	<table border="0"> <thead> <tr> <th>Material</th> <th>Weight [kg]</th> </tr> </thead> <tbody> <tr> <td>Paper / Cardboard</td> <td>x.42</td> </tr> <tr> <td>Plastic Foamed PE</td> <td>x.39</td> </tr> <tr> <td>Plastic PE</td> <td>x.13</td> </tr> <tr> <td>Others</td> <td>x.03</td> </tr> </tbody> </table> <p>Packaging material is free of PVC</p>	Material	Weight [kg]	Paper / Cardboard	x.42	Plastic Foamed PE	x.39	Plastic PE	x.13	Others	x.03	
Material	Weight [kg]												
Paper / Cardboard	x.42												
Plastic Foamed PE	x.39												
Plastic PE	x.13												
Others	x.03												
5.9	Disassembly/Recycling:	<p>Mechanical plastic parts weighing more than 25g are marked according to ISO 11469.</p> <p>Of total plastic parts' weight &gt;25g, recycled material content percentage is between 5% to 10%.</p>											
5.10	Take back information:	The supplier offers take back and recycling services for products and consumables in many locations throughout the world. Customers are advised to contact their supplier representatives for additional information.											
5.11	Documentation:	The documentation is available as printout on Totally Chlorine Free bleached paper or as electronic file. <a href="https://manuals.konicaminolta.eu/konicaminolta">https://manuals.konicaminolta.eu/konicaminolta</a>											